

RETRANSFER
PRINTER

MATICA



XID8300





XID8300

RETRANSFER PRINTER

The modular single- or double-sided *EDIssecure*® XID8300 Retransfer Printer was developed for industrial needs, thus it is provided with various optional modules such as bend remedy, flipper, and encoding modules. Based on wealth and experience with XID Retransfer Technology, the printer is ready for plug and play inline encoding and lamination. With its compact size, the printer delivers the right combination of reliability, performance and affordability for printing durable and secure cards. It almost achieves offset printing quality, even on uneven surface of smart cards.

The XID8300 prints on a variety of card materials including long-lasting, durable non-PVC cards such as ABS, PET, and Polycarbonate. The lockable, spacious card hopper stores up to 200 blank cards to secure an interrupt-free workflow. The user-friendly front-loading system with replaceable cartridges makes changing of supplies fast and simple.

The printer is ready to meet your individual requirements and can be equipped according to the customer needs. Optional magnetic stripe, IC contact and smart card encoding is possible for further demands on card functionality. Extend the life time and security of your cards by joining the printer with the *EDIssecure*® Inline Lamination Modules ILM-LS for single-sided lamination and ILM-DS for simultaneous dual side lamination.

Diverse security features such as electronic security lock, Ken-sington-lock, dye-sublimation UV ink ribbon for invisible security printing, IPSEC for encrypted data transfer through networks, and Security Erase of black data on used supplies help to secure the environment and cards from counterfeiting and to avoid misuse of personal information.

TECHNICAL SPECIFICATIONS

Print Method

Dye-sublimation retransfer

Print Mode

Single- or double-sided (optional) over-the-edge retransfer printing

Print Resolution

300 dpi

Print Speed

Up to 120 cards per hour (single-sided)

Card Types

PVC, Composite PVC, ABS, PET and Polycarbonate Cards of ISO ID -1/CR-80 size, 85.60 x 53.98 mm

Card Thickness

0.25 - 1.02 mm (hopper adjustment required)

Input Hopper Capacity

200 cards (0.76 mm)

Output Hopper Capacity

100 cards (0.76 mm)

Interface

USB 2.0 and Ethernet

Operating System Support

Windows 7, 8, 10 (32 & 64bits)

Power Supply

100/120V and 220/240 V, 50/60 Hz FCC, CE, UL, GOST-R, and CCC approved

Operating Environment

15°C to 30°C, 35% to 70% noncondensing humidity

Printer Dimensions

343 x 322 x 360 mm (WxDxH)

Weight

13.9 kg (excluding optional built-in items)

Warranty

Printer: 36 months

Printhead: Lifetime warranty using *EDIssecure*® materials (other conditions apply)

*Attention: The use of non-Matica brand ribbons could adversely affect the performance of your Matica hardware and void the products warranty.